

Standard workbench XXL

Provides plenty of space for large items.



Standard workbench with extra wide drawers. Stationary and mobile version. Load capacity up to 2000 kg depending on version.

Stationary standard workbench XXL

- Cabinet housing in a sturdy steel plate construction 1205 × 695 × 600 mm (W × D × H)
- Drawers with 100 % full extension and a load capacity of 75 to 200 kg (optional)
- „Key Lock” central lock with single-drawer blocking system
- Workbench leg assembly made of robust tubing 50 × 50 × 205 mm (W × D × H)
- Supplied fully assembled
- Optionally available with height adjustment (840–1190 mm)
- Optionally available with levelling feet (adjustability 40–90 mm)
- Load capacity up to 2000 kg (with an evenly distributed surface load)
- Available with either Multiplex 40 workbench top or 50 mm beechblock. Other tops available on request
- Top depth 700 mm. Depths of 750 and 800 mm available on request



Art. No. **51.806.502**
Anthracite grey, RAL 7016
Pale grey, RAL 7035

Optionally available



Wide range of drawer partition materials



TM-RIFD electronic central lock

Workbench superstructures with diverse configuration options



| Specification | Top thickness mm | Width mm | Height mm | Drawers | Art. no. |
|---------------|------------------|----------|-----------|---------------------------------------|-------------------|
| Multiplex | 40 | 1500 | 840 | 2 × FH 100, 75 kg / 2 × FH 150, 75 kg | 51.806.+++ |
| Beech block | 50 | 1500 | 850 | 2 × FH 100, 75 kg / 2 × FH 150, 75 kg | 51.854.+++ |

Mobile standard workbench XXL

- Cabinet housing in a sturdy steel plate construction
- Drawers with 100 % full extension and a load capacity of maximum 75 kg
- Cabinet housing 1205 × 695 × 600 mm (W × D × H)
- „Key Lock” central lock with single-drawer blocking system
- Workbench leg assembly made of robust tubing 50 × 50 × 205 mm (W × D × H)
- Supplied fully assembled
- Swivel castors with hinged turning lever for mobile or stationary use
- Includes safety catch on the right to prevent drawers from unintentionally opening while moving the workbench.
- Load capacity up to 400 kg (with an evenly distributed surface load)
- Top depth 700 mm. Depths of 750 and 800 mm available on request
- Available with either Multiplex 40 workbench top or 50 mm beechblock. Other tops available on request

Optionally available



Wide range of drawer partition materials



TM-RIFD electronic central lock



Rear panel, height 150 mm, multiplex 20 mm



Art. no. **51.827.501**
Pigeon blue, NCS S 4040-R70 B
Light blue, NCS S 1060-R80 B

| Specification | Top thickness mm | Width mm | Height mm | Drawers | Art. no. |
|---------------|------------------|----------|-----------|---------------------------------------|-------------------|
| Multiplex | 40 | 1500 | 870/890 | 2 × FH 100, 75 kg / 2 × FH 150, 75 kg | 51.827.+++ |
| Beech block | 50 | 1500 | 880/900 | 2 × FH 100, 75 kg / 2 × FH 150, 75 kg | 51.847.+++ |

.502

Housing: Anthracite grey, RAL 7016
Doors: Pale grey, RAL 7035

.501

Housing: Pigeon blue, NCS 4040
Doors: Light blue, NCS 1060

